



CCSDS SM&C Mission Operations Interoperability Prototype

Space Ops 2010

Steven A. Lucord

April 30, 2010




Introduction

- Future manned missions present unique challenges:
 - Require interoperability among space agencies
 - Reduced budgets for operations and development
- Mission Operations identifies two benefits of interest:
 - Increase interoperability among space agencies
 - Reduced cost of mission-specific deployment
- Interoperability Prototype covers three main topics:
 - Validation of the Mission Operations Protocol
 - Integration of legacy systems in an SOA
 - Exploration of the Data Distribution Service



Motivation

- Common exchange format between NASA control centers is necessary
- Investigating ground-to-ground standardization
- Negotiation of an data exchange format between control centers can be challenging.






Validation of MO Protocols

- Collaborate with the German Space Operations Center (DLR) to implement an interoperability prototype
 - Prototype implements five MO services:
 - Action Service
 - Parameter Service
 - Alert Service
 - Directory Service
 - Login Service (internal access control)
- Identify additional capabilities for the services to meet human spaceflight operations concepts




Action, Alert and Parameter Service Architecture


JSC-OTF



Transport Bridge




DLR-GSOC






Directory Service Architecture

JSC-OTF



DLR-GSOC






Encoding Specifications

- Encoding is currently mission implementation specific
- Developed a BNF like grammar to describe a binary encoding with emphasis on simplicity
- Developed an XML schema for encoding of the data structures necessary for the Directory Service




Bridging System Domains



- Use an “in care of” address to specify the routing information
 - `otf-service-uri@otf-gateway-uri`
- The Message Header URI contains the complete routing sequence similar to USENET addresses



In Care of Address Example



URI to
ddsbinsbin:action-service@
jmsbinsbin:otf-gateway@
URI to
jmsbinsbin:dlr-gateway
URI from
jmsbinsbin:action-client
URI from
ddsbinsbin:action-service@
jmsbinsbin:otf-gateway@
jmsbinsbin:dlr-gateway

URI to
ddsbinsbin:action-service@
jmsbinsbin:otf-gateway
URI to
jmsbinsbin:action-client@
jmsbinsbin:dlr-gateway
URI from
jmsbinsbin:action-client@
jmsbinsbin:dlr-gateway
URI from
ddsbinsbin:action-service@
jmsbinsbin:otf-gateway

URI to
ddsbinsbin:action-service
URI to
jmsbinsbin:action-client@
jmsbinsbin:dlr-gateway@
URI from
jmsbinsbin:action-client@
jmsbinsbin:dlr-gateway@
URI from
ddsbinsbin:action-service



Additional Capabilities

- Human spaceflight requirements for Action Service
- Significant departure from traditional unmanned environment:
 - Control a few number of resources with a large number of people
 - Consequences of sending the incorrect command are more serious when humans are aboard
 - Provides a distributed work environment to allow flight controllers and operators to collaborate
 - Maintain a dynamic and shared command repository




Integrating Legacy Systems

- Action Service interfaces with the ISS Command Server
 - Treated as just another client
 - Identified a set of eleven Station commands
- Parameter Service interfaces with the telemetry distribution system for ISS and the Space Shuttle
 - Identified a set of twenty corresponding ISS telemetry parameters
- Alert Service interfaces with the advisory service for ISS and the Space Shuttle.




Prototype Architecture





Bridging Control Centers






Extend Prototype Bridge

- Prototype bridge solution requires knowledge of complete routing sequence
- Extend solution to accommodate an arbitrary number of gateways.
- Maintain only the next hop routing information in the URI




Bridge Publish Availability





Bridge Request / Reply






Data Distribution Service

- Prototype uses for bulk data transfer
- Plan to perform benchmark comparisons against legacy telemetry distribution system
- Investigate structured data messages



Transport Broker





Conclusion

- Specifications are sufficiently robust to allow NASA missions to collaborate
- Specifications are not yet capable of replacing existing systems
- Encourage NASA space centers to participate in the working group and propose capabilities necessary for mission support



Thank You

- Questions